





Junior Metallsägenwerk C. Mesenhöller GmbH & Co. KG

### BAND SAW BLADE SELECTION & TECHNICAL SERVICE

How to select the right blade size



#### LENGTH I WIDTHS I THICKNESS

Best to be found in the machine manual.

## Product grade How to select the right



MULTICUT M42 General cutting of solid and structural materials.



PROBEAM M42
Special blade to cut structural materials and smaller work pieces.

for Bimetal Band Saw Blades

General advice



DUROCUT M51
Special blade to cut high and highest alloyed solid materials.

Interested in Tungsten Carbide Products / TCT ?
Please let us have details on your sawing application to work out the best & customized solution for you.

## 3 How to select the right tooth pitch

Solid material



	D	tpi
<	25 mm	10/14
15 –	40 mm	8/12
25 –	50 mm	6/10
35 -	70 mm	5/8
40 -	90 mm	5/6
50 -	120 mm	4/6
80 -	150 mm	3/4
130 -	350 mm	2/3
150 –	450 mm	1,5/2
200 -	600 mm	1,1/1,6
>	500 mm	0,75/1,25

#### **Tubes & Profiles**

↓ S mm	→ D mm									
	20	40	60	80	100	120	150	200	300	500
2	14	12/16 P	12/16 P	12/16 P	12/16 P	8/11P	8/11P	8/11P	8/11P	5/7P
3	14	12/16 P	12/16 P	8/11P	8/11P	8/11P	8/11P	5/7P	5/7P	5/7P
4	12/16 P	12/16 P	8/11P	8/11P	8/11P	5/7P	5/7P	5/7P	5/7P	4/6P
5	12/16 P	12/16 P	8/11P	8/11P	5/7P	5/7P	5/7P	4/6P	4/6P	4/6F
6	12/16 P	8/11P	8/11P	5/7P	5/7P	5/7P	5/7P	4/6P	4/6P	4/6F
8	12/16 P	8/11P	8/11P	5/7P	5/7P	5/7P	4/6P	4/6P	4/6P	4/6F
10		8/11P	5/7P	5/7P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6F
12		8/11P	5/7P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6
15		8/11P	5/7P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6
20			4/6P	4/6P	4/6P	4/6P	4/6P	4/6P	4/6P	3/4
30				4/6P	4/6P	4/5P	4/6P	4/6P	4/6P	2/3F
50							4/6P	3/4P	2/3P	2/3
80								3/4P	2/3P	2/31
>100									2/3P	1,5/

# 4 How to find the best cutting parameters



#### **SPEED & FEED RATES, COOLANT**

Based on your application.

See you at **Cut IT**, the cutting database by Junior.



## 5 How to get technical support





#### **VISIT THE JUNIOR SERVICE AREA**

Videos to help you with your challenges. If you have any questions, your distributor will be happy to help.



